

piGRIP® G.S35T50.B1.S1.G14M.00.FDA



- ▶ Configurable suction cup with recyclable parts. The different hardness makes the suction cup stable and at the same time soft and flexible.
- ▶ Durable and long lasting material with higher lifting capacity compared to similar conventional cups.
- ▶ Suitable for curved parts with a slightly coarse surface such as textured plastic parts.
- ▶ Suitable for level adjustment and to separate thin objects.

Lifting force

Description	Vertical		Parallel	
	40 -kPa	60 -kPa	40 -kPa	60 -kPa
Lifting forces	24.0 N	34.5 N	12.0 N	17.2 N

Technical data

Description	Unit	Value
Max. vertical movement	mm	7.2
Internal volume	cm ³	7.0
Weight	g	18.3
Min. Curve radius -60 kPa	mm	17

Material specification

Description	Material	Colour	Hardness °Shore A	Temperature range (°C)
Lip	TPE	Blue	50	-40-60/100*
Bellow	TPE	Transparent	87	-20-60/100*
Support	TPE	Transparent	80	-20-60/100*
Fitting	Al, NBR	-	-	-20-90

*Max. Temperature short term contact, <10 seconds and 50% intermittence, ambient temperature 15-30°C, mechanical properties will start to degrade.

Material resistance

Description	FDA Approved	PWIS Free	Wear Resistance	Oil	Weather & Ozone
Lip	Yes	No	Fair	Poor	Excellent
Bellow	Yes	Yes	Excellent	Excellent	Excellent
Support	Yes	Yes	Excellent	Excellent	Excellent

Description	Hydrolysis	Petrol	Concentrated Acids	Alcohol	Oxidation
Lip	Poor	Poor	Poor	Excellent	Good
Bellow	Fair	Poor	Poor	Good	Good
Support	Fair	Poor	Poor	Good	Good

Values specified in data sheet are tested at:

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).
- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.

Dimensional drawing



Description	Unit	Value
Building height	mm	29.3
Building height (no fitting)	mm	23.3
Diameter (lip)	mm	35
Wrench key (fitting)	mm	SW 22

Ordering information

Description	Product code
piGRIP®, Ø 35 mm Standard lip, TPE 50° Shore A, Blue, Bellows 1 fold, Support S1, G-Thread, 1/4", Male, No Option, FDA 21 CFR 177.2600 & EU 1935/2004	G.S35T50.B1.S1.G14M.00.FDA

Ordering information, spare parts

Description	Art. No.
Ø 35 mm Standard lip, TPE 50° Shore A	0122131