

Vacuum pump MINI X40L, conn. K, NBR sealings, 0100423



- Extra vacuum level to 93 -kPa
- Small size and low weight
- Use in tightly sealed or non-porous applications

General

Material	ABS, NBR (FKM), PA, POM, SS, Al
Noise level	60 – 70 dBA
Temperature	-20 – 80 °C
Weight, max.	420 g


Vacuum flow

Feed pressure	Air consumption	Vacuum flow (NL/s) at different vacuum levels (-kPa)										Max vacuum
		0	10	20	30	40	50	60	70	80	90	
MPa	Nl/s	0	1.5	1	0.9	0.7	0.6	0.5	0.4	0.17	0.038	-kPa
0.4	3.1	3.2	1.5	1	0.9	0.7	0.6	0.5	0.4	0.17	0.038	93

Evacuation time

Feed pressure	Air consumption	Evacuation time (s/l) to reach different vacuum levels (-kPa)									Max vacuum
		10	20	30	40	50	60	70	80	90	
MPa	Nl/s	10	20	30	40	50	60	70	80	90	-kPa
0.4	3.1	0.038	0.12	0.22	0.33	0.48	0.68	1.2	2.2	3.2	93

Dimensional drawings



Values specified in the data sheet are tested at:

Room temperature	(20°C [68°F] ± 3°C [5.5°F])
Standard atmosphere	(101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
Relative humidity	0-100%
Compressed air quality	DIN ISO 8573-1 class 4

Spare parts

	Item no.
Sealing kit MINI 30-60, NBR	0100491