


**ERDT10/16**


Width: 11 mm



10-16 mm² Feed Through Terminal Block  
1 In, 3 Out  
For 35 mm DIN and DIN Rail

**ERDT-S10/16**

Width: 11 mm



10-16 mm² Feed Through Terminal Block  
1 In, 3 Out  
Not Suitable for Rail

**ERDT10/16-2**

Width: 23.5 - 34.5 - 45.5 - 56.5 mm



10-16 mm² Feed Through Terminal Block  
1 In, 3 Out, 2 Pieces  
For 35 mm DIN and DIN Rail

**ERDT10/16-3**

Width: 23.5 - 34.5 - 45.5 - 56.5 mm



10-16 mm² Feed Through Terminal Block  
1 In, 3 Out, 3 Pieces  
For 35 mm DIN and DIN Rail

**ERDT10/16-4**

Width: 23.5 - 34.5 - 45.5 - 56.5 mm



10-16 mm² Feed Through Terminal Block  
1 In, 3 Out, 4 Pieces  
For 35 mm DIN and DIN Rail

**ERDT10/16-5**

Width: 23.5 - 34.5 - 45.5 - 56.5 mm



10-16 mm² Feed Through Terminal Block  
1 In, 3 Out, 5 Pieces  
For 35 mm DIN and DIN Rail



Electrical Ratings	Voltage, V ~	Current, A	Cross Section
CE (EN 60947-7-1)	750	76	16 mm²
UL/ULC			
VDE (IEC 60947-7-1)			
CSA			
ES3x			

Dimensional Data	
Conductor cross section solid (min.-max.)	2.5 - 0.5 mm²
Conductor cross section stranded (min.-max.)	25 - 16 mm²
2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.)	1.5 - 0.5 / 10 - 6 mm²
AWG Conductor	AWG 14/20 - 4/6
Insulation Stripping Length	14/8 - 16/10 mm
Torque (min.-max.)	1.2/1.2 - 2.0/1.8 Nm
Screwdriver	0.8 x 4.0

Technical Data	
Rated Impulse Voltage	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B6
Protection class / Protection conductor type	IP 20 / -

Ordering Data	Terminal	Qty.	End Plate	Qty.
Beige	ERDT10/16BEIGE	20	EPDTBEIGE	10




Cross Connection - Comb Connection	Part Number	Qty.	Part Number	Qty.

End Bracket	Part Number	Qty.	Part Number	Qty.
xx Beige or Grey	ES1xx	100	ES4xx	100
	ES3xx	100	ES3xx	100



Red Plug and Sockets	Part Number	Qty.	Part Number	Qty.




Warning Label	With Symbol	Qty.	Without Symbol	Qty.
Available in White and Yellow				



Group Marking	Part Number	Qty.	Part Number	Qty.
GM	GM	50	GM	50
GM1-1	GM1-1	25	GM1-1	25
GM1-2	GM1-2	25	GM1-2	25
GM2-2	GM2-2	25	GM2-2	25



Unprinted Markers	Part Number	Qty.	Part Number	Qty.



Voltage, V ~	Current, A	Cross Section
750	76	16 mm²

Dimensional Data	
Conductor cross section solid (min.-max.)	2.5 - 0.5 mm²
Conductor cross section stranded (min.-max.)	25 - 16 mm²
2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.)	1.5 - 0.5 / 10 - 6 mm²
AWG Conductor	AWG 14/20 - 4/6
Insulation Stripping Length	14/8 - 16/10 mm
Torque (min.-max.)	1.2/1.2 - 2.0/1.8 Nm
Screwdriver	0.8 x 4.0

Technical Data	
Rated Impulse Voltage	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B6
Protection class / Protection conductor type	IP 20 / -

Ordering Data	Terminal	Qty.	End Plate	Qty.
	ERDT-S10/16BEIGE	20	EPDTBEIGE	10

Cross Connection - Comb Connection	Part Number	Qty.	Part Number	Qty.

End Bracket	Part Number	Qty.	Part Number	Qty.
	ES1xx	100	ES4xx	100
	ES3xx	100	ES3xx	100

Red Plug and Sockets	Part Number	Qty.	Part Number	Qty.

Warning Label	With Symbol	Qty.	Without Symbol	Qty.

Group Marking	Part Number	Qty.	Part Number	Qty.
GM	GM	50	GM	50
GM1-1	GM1-1	25	GM1-1	25
GM1-2	GM1-2	25	GM1-2	25
GM2-2	GM2-2	25	GM2-2	25

Unprinted Markers	Part Number	Qty.	Part Number	Qty.

Voltage, V ~	Current, A	Cross Section
750	76	16 mm²

Dimensional Data	
Conductor cross section solid (min.-max.)	2.5 - 0.5 mm²
Conductor cross section stranded (min.-max.)	25 - 16 mm²
2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.)	1.5 - 0.5 / 10 - 6 mm²
AWG Conductor	AWG 14/20 - 4/6
Insulation Stripping Length	14/8 - 16/10 mm
Torque (min.-max.)	1.2/1.2 - 2.0/1.8 Nm
Screwdriver	0.8 x 4.0

Technical Data	
Rated Impulse Voltage	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B6
Protection class / Protection conductor type	IP 20 / -

Ordering Data	Terminal	Qty.	End Plate	Qty.
	ERDT10/16-2BEIGE	20	EPDTBEIGE	10

Cross Connection - Comb Connection	Part Number	Qty.	Part Number	Qty.

End Bracket	Part Number	Qty.	Part Number	Qty.
	ES1xx	100	ES4xx	100
	ES3xx	100	ES3xx	100

Red Plug and Sockets	Part Number	Qty.	Part Number	Qty.

Warning Label	With Symbol	Qty.	Without Symbol	Qty.

Group Marking	Part Number	Qty.	Part Number	Qty.
GM	GM	50	GM	50
GM1-1	GM1-1	25	GM1-1	25
GM1-2	GM1-2	25	GM1-2	25
GM2-2	GM2-2	25	GM2-2	25

Unprinted Markers	Part Number	Qty.	Part Number	Qty.

Voltage, V ~	Current, A	Cross Section
750	76	16 mm²

Dimensional Data	
Conductor cross section solid (min.-max.)	2.5 - 0.5 mm²
Conductor cross section stranded (min.-max.)	25 - 16 mm²
2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.)	1.5 - 0.5 / 10 - 6 mm²
AWG Conductor	AWG 14/20 - 4/6
Insulation Stripping Length	14/8 - 16/10 mm
Torque (min.-max.)	1.2/1.2 - 2.0/1.8 Nm
Screwdriver	0.8 x 4.0

Technical Data	
Rated Impulse Voltage	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B6
Protection class / Protection conductor type	IP 20 / -

Ordering Data	Terminal	Qty.	End Plate	Qty.
	ERDT10/16-3BEIGE	20	EPDTBEIGE	10

Cross Connection - Comb Connection	Part Number	Qty.	Part Number	Qty.

End Bracket	Part Number	Qty.	Part Number	Qty.
	ES1xx	100	ES4xx	100
	ES3xx	100	ES3xx	100

Red Plug and Sockets	Part Number	Qty.	Part Number	Qty.

Warning Label	With Symbol	Qty.	Without Symbol	Qty.

Group Marking	Part Number	Qty.	Part Number	Qty.
GM	GM	50	GM	50
GM1-1	GM1-1	25	GM1-1	25
GM1-2	GM1-2	25	GM1-2	25
GM2-2	GM2-2	25	GM2-2	25

Unprinted Markers	Part Number	Qty.	Part Number	Qty.

Voltage, V ~	Current, A	Cross Section
750	76	16 mm²

Dimensional Data	
Conductor cross section solid (min.-max.)	2.5 - 0.5 mm²
Conductor cross section stranded (min.-max.)	25 - 16 mm²
2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.)	1.5 - 0.5 / 10 - 6 mm²
AWG Conductor	AWG 14/20 - 4/6
Insulation Stripping Length	14/8 - 16/10 mm
Torque (min.-max.)	1.2/1.2 - 2.0/1.8 Nm
Screwdriver	0.8 x 4.0

Technical Data	
Rated Impulse Voltage	8/3
Insulation material group / Gauge pin code according to IEC 60947-1	1/B6
Protection class / Protection conductor type	IP 20 / -

Ordering Data	Terminal	Qty.	End Plate	Qty.
	ERDT10/16-4BEIGE	20	EPDTBEIGE	10

Cross Connection - Comb Connection	Part Number	Qty.	Part Number	Qty.

End Bracket	Part Number	Qty.	Part Number	Qty.
	ES1xx	100	ES4xx	100
	ES3xx	100	ES3xx	100

Red Plug and Sockets	Part Number	Qty.	Part Number	Qty.

Warning Label	With Symbol	Qty.	Without Symbol	Qty.

Group Marking	Part Number	Qty.	Part Number	Qty.
GM	GM	50	GM	50
GM1-1	GM1-1	25	GM1-1	25
GM1-2	GM1-2	25	GM1-2	25
GM2-2	GM2-2	25	GM2-2	25

Unprinted Markers	Part Number	Qty.	Part Number	Qty.