



6 mm² Disconnect Terminal Block with Bushbar
For 35 mm D and DIN Rail



4 mm² Knife Disconnect Terminal Block
For 35 mm DIN Rail



2.5 mm² Disconnect Terminal Block
1 In, 2 Out
For 35 mm DIN Rail



2.5 mm² Disconnect Terminal Block
2 In, 2 Out
For 35 mm DIN Rail



2.5 mm² Knife Disconnect Terminal Block
For 35 mm DIN Rail



4 mm² Knife Disconnect Terminal Block
1 In, 2 Out
For 35 mm DIN Rail



| Electrical Ratings | Voltage, V ~ | Current, A | Cross Section |
|---------------------|--------------|------------|-------------------|
| GE (EN 60947-7-1) | 500 | 6.3 | 6 mm ² |
| UL/ULC | 300 | 6.3 | AWG 26-8 |
| VDE (IEC 60947-7-1) | | | |
| CSA | | | |
| ESCA | | | |

| Dimensional Data | Value |
|---|--------------------------|
| Conductor cross section solid (min.-max.) | 0.2 - 10 mm ² |
| Conductor cross section stranded (min.-max.) | 0.2 - 10 mm ² |
| 2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.) | 0.5 - 4 mm ² |
| AWG Conductor | AWG 24 - 8 |
| Insulation Stripping Length | 10 - 12 mm |
| Torque (min.-max.) | 0.8 - 1.2 Nm |
| Screwdriver | 0.8 x 3.5 |

| Technical Data | Value |
|--|-----------|
| Rated Impulse Voltage | 6/3 |
| Insulation material group / Gauge pin code according to IEC 60947-1 | 1/BS |
| Protection class / Protection conductor type | IP 20 / - |

| Ordering Data | Terminal | Qty. | End Plate | Qty. |
|---------------|-----------|-----------|-----------|------|
| ERTD2BEIGE | 25 | EPF2BEIGE | 25 | |
| | ERTD2GREY | 25 | EPF2GREY | 25 |



| Terminal | Qty. | End Plate | Qty. |
|------------|------|-----------|------|
| ERTD4BEIGE | 50 | EPF2BEIGE | 10 |
| ERTD4GREY | 50 | EPF2GREY | 10 |

| Terminal | Qty. | End Plate | Qty. |
|----------------|------|---------------|------|
| ERTD2.5SDBEIGE | 80 | EPF2.5SDBEIGE | 25 |
| ERTD2.5SDGREY | 80 | EPF2.5SDGREY | 25 |

| Terminal | Qty. | End Plate | Qty. |
|----------------|------|---------------|------|
| ERTD2.5DDBEIGE | 80 | EPF2.5DDBEIGE | 25 |
| ERTD2.5DDGREY | 80 | EPF2.5DDGREY | 25 |

| Terminal | Qty. | End Plate | Qty. |
|---------------|------|--------------|------|
| ERTD2.5KBEIGE | 50 | EPF2.5KBEIGE | 25 |
| ERTD2.5KGREY | 50 | EPF2.5KGREY | 25 |

| Terminal | Qty. | End Plate | Qty. |
|--------------|------|-------------|------|
| ERTD4SDBEIGE | 50 | EPF4SDBEIGE | 25 |
| ERTD4SDGREY | 50 | EPF4SDGREY | 25 |

| Terminal | Qty. | End Plate | Qty. |
|--------------|------|-------------|------|
| ERTD4SDBEIGE | 50 | EPF4SDBEIGE | 25 |
| ERTD4SDGREY | 50 | EPF4SDGREY | 25 |

| Cross Connection - Comb Connection | Part Number | Qty. | Part Number | Qty. |
|------------------------------------|-------------|------|-------------|------|
| | CCS4/2 | 25 | | |
| | CCS4/3 | 20 | | |
| | CCS4/4 | 15 | | |



| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| CCS4/2 | 25 | | |
| CCS4/3 | 20 | | |
| CCS4/4 | 15 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES1xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |
| ES3xx | 100 | | |

| Fail Bracket xx, Single or Grey | Part Number | Qty. | Part Number | Qty. |
|---------------------------------|-------------|------|-------------|------|
| | ES1xx | 100 | | |
| | ES4xx | 100 | | |
| | ES7xx | 50 | | |
| | ES3xx | 100 | | |



| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES1xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |
| ES3xx | 100 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES1xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |
| ES3xx | 100 | | |

| Tool Plug and Sockets | Part Number | Qty. | Part Number | Qty. |
|-----------------------|-------------|------|-------------|------|
| | | | | |



| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| Warning Label Available in White and Yellow | Part Number | Qty. | Part Number | Qty. |
|---|-------------|------|-------------|------|
| | | | | |



| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| Group Marking | Part Number | Qty. | Part Number | Qty. |
|---------------|-------------|------|-------------|------|
| | GM | 50 | GM3 | 50 |
| | GM1-1 | 25 | | |
| | GM1-2 | 25 | | |
| | GM2-1 | 25 | | |
| | GM2-2 | 25 | | |



| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| GM | 50 | | |
| GM1-1 | 25 | | |
| GM1-2 | 25 | | |
| GM2-1 | 25 | | |
| GM2-2 | 25 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| GM | 50 | | |
| GM1-1 | 25 | | |
| GM1-2 | 25 | | |
| GM2-1 | 25 | | |
| GM2-2 | 25 | | |

| Deprinted Markers | Part Number | Qty. | Part Number | Qty. |
|-------------------|-------------|------|-------------|------|
| | DG10/5 | 280 | | |
| | DG10/6 | 350 | | |



| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/5 | 280 | | |
| DG10/6 | 350 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/5 | 280 | | |
| DG10/6 | 350 | | |

| Terminal | Qty. | End Plate | Qty. |
|----------------|------|---------------|------|
| ERTD2.5SDBEIGE | 80 | EPF2.5SDBEIGE | 25 |
| ERTD2.5SDGREY | 80 | EPF2.5SDGREY | 25 |

| Terminal | Qty. | End Plate | Qty. |
|----------------|------|---------------|------|
| ERTD2.5DDBEIGE | 80 | EPF2.5DDBEIGE | 25 |
| ERTD2.5DDGREY | 80 | EPF2.5DDGREY | 25 |

| Terminal | Qty. | End Plate | Qty. |
|---------------|------|--------------|------|
| ERTD2.5KBEIGE | 50 | EPF2.5KBEIGE | 25 |
| ERTD2.5KGREY | 50 | EPF2.5KGREY | 25 |

| Terminal | Qty. | End Plate | Qty. |
|--------------|------|-------------|------|
| ERTD4SDBEIGE | 50 | EPF4SDBEIGE | 25 |
| ERTD4SDGREY | 50 | EPF4SDGREY | 25 |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| CCS2 5/2 | 25 | | |
| CCS2 5/3 | 20 | | |
| CCS2 5/4 | 5 | | |
| CCS2 5/10 | 5 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES1xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES1xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES1xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/5 | 440 | | |
| DG10/6 | 350 | | |


| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/5 | 440 | | |
| DG10/6 | 350 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/5 | 440 | | |
| DG10/6 | 350 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/5 | 440 | | |
| DG10/6 | 350 | | |

ERTD4DD


Width: 6 mm



4 mm² Knife Disconnect Terminal Block
2 In, 2 Out
For 35 mm DIN Rail

ERTD4SKT


Width: 5.8 mm



Socket for ERTD4DD and ERTD4A

ERTD4SKTD


Width: 5.8 mm



Socket for ERTD4DD and ERTD4A
with Diode

ERTD4A


Width: 6 mm



4 mm² Knife Disconnect Terminal Block
For 35 mm DIN Rail

ERTD6B

Width: 10 mm



6 mm² Knife Disconnect Terminal Block
with Busbar
For 35 mm DIN Rail

ERTD3

Width: 6.2 mm



4 mm² Disconnect Terminal Block
with Socket and Busbar
For 35 mm DIN Rail



Electrical Ratings
GE (EN 60947-7-1)
UL1818
VDE (IEC 60947-7-1)
CSA
ESIX

Connection Data

Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length
Torque (min.-max.)
Screwdriver

Technical Data

Rated Impulse Voltage
Insulation material group /
Gauge per code according to IEC 60947-1
Protection class / Protection conductor type

Diode Technical Data

Diode Voltage
Diode Current
Diode

Ordering Data

Beige
Grey



| Voltage, V ~ | Current, A | Cross Section |
|--------------|------------|-------------------|
| 500 | 20 | 4 mm ² |

| Conductor cross section solid (min.-max.) | Conductor cross section stranded (min.-max.) | 2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.) | AWG Conductor | Insulation Stripping Length | Torque (min.-max.) | Screwdriver |
|---|--|---|---------------|-----------------------------|--------------------|-------------|
| 0.2 - 6 mm ² | 0.2 - 6 mm ² | 0.5 - 2.5 mm ² | AWG 24 - 10 | 9 - 10 mm | 0.5 - 0.8 Nm | 0.8 x 3.5 |

| Rated Impulse Voltage | Insulation material group / Gauge per code according to IEC 60947-1 | Protection class / Protection conductor type |
|-----------------------|---|--|
| 6/3 | 1/A4 | IP 20 / - |

| Diode Voltage | Diode Current | Diode |
|---------------|---------------|-------|
| | | |

| Terminal | Qty. | End Plate | Qty. |
|--------------|------|-------------|------|
| ERTD4DDBEIGE | 50 | EP4TDDBEIGE | 25 |
| ERTD4DDGREY | 50 | EP4TDDGREY | 25 |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| CCS4/2 | 25 | | |
| CCS4/3 | 20 | | |
| CCS4/4 | 15 | | |
| CCS4/10 | 5 | | |

Cross Connection - Comb Connection



End Bracket

xx Beige or Grey



| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES7xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |

Test Plug and Sockets



| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| | | | |

Warning Label

Available in White and Yellow



| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

Group Marking



| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| | | | |

Unprinted Markers



| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/5 | 440 | MT10/5 | 500 |
| DG10/6 | 360 | DG10/6 | 360 |

| Voltage, V ~ | Current, A | Cross Section |
|--------------|------------|---------------------|
| 400 | 0.5 | 2.5 mm ² |

| Conductor cross section solid (min.-max.) | Conductor cross section stranded (min.-max.) | 2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.) | AWG Conductor | Insulation Stripping Length | Torque (min.-max.) | Screwdriver |
|---|--|---|---------------|-----------------------------|--------------------|-------------|
| 0.2 - 4 mm ² | 0.2 - 4 mm ² | 0.5 - 1.5 mm ² | AWG 24 - 12 | 6 - 7 mm | 0.4 - 0.5 Nm | 0.8 x 3.5 |

| Rated Impulse Voltage | Insulation material group / Gauge per code according to IEC 60947-1 | Protection class / Protection conductor type |
|-----------------------|---|--|
| 6/3 | 1/A3 | IP 20/ PE |

| Diode Voltage | Diode Current | Diode |
|---------------|---------------|----------|
| 1000 V | 0.5 A | 1 N 4007 |

| Terminal | Qty. | End Plate | Qty. |
|---------------|------|-------------|------|
| ERTD4SKTBEIGE | 50 | EP4SKTBEIGE | 25 |
| ERTD4SKTGREY | 50 | EP4SKTGREY | 25 |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| CCS4/2 | 25 | | |
| CCS4/3 | 20 | | |
| CCS4/4 | 15 | | |
| CCS4/10 | 5 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES7xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| | | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/5 | 500 | DG10/5 | 360 |
| DG10/6 | 360 | DG10/6 | 360 |

| Voltage, V ~ | Current, A | Cross Section |
|--------------|------------|-------------------|
| 500 | 20 | 4 mm ² |
| 300 | 16 | AWG 20 - 10 |

| Conductor cross section solid (min.-max.) | Conductor cross section stranded (min.-max.) | 2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.) | AWG Conductor | Insulation Stripping Length | Torque (min.-max.) | Screwdriver |
|---|--|---|---------------|-----------------------------|--------------------|-------------|
| 0.2 - 6 mm ² | 0.2 - 4 mm ² | 0.5 - 2.5 mm ² | AWG 24 - 10 | 9 - 10 mm | 0.5 - 0.8 Nm | 0.8 x 3.5 |

| Rated Impulse Voltage | Insulation material group / Gauge per code according to IEC 60947-1 | Protection class / Protection conductor type |
|-----------------------|---|--|
| 6/3 | 1/A4 | IP 20/ - |

| Diode Voltage | Diode Current | Diode |
|---------------|---------------|-------|
| | | |

| Terminal | Qty. | End Plate | Qty. |
|-------------|------|------------|------|
| ERTD4ABEIGE | 50 | EPF4ABEIGE | 25 |
| ERTD4AGREY | 50 | EPF4AGREY | 25 |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| CCS4/2 | 25 | | |
| CCS4/3 | 20 | | |
| CCS4/4 | 15 | | |
| CCS4/10 | 5 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES7xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| | | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/5 | 440 | DG10/5 | 360 |
| DG10/6 | 360 | DG10/6 | 360 |

| Voltage, V ~ | Current, A | Cross Section |
|--------------|------------|-------------------|
| 750 | 6.3 | 6 mm ² |
| 600 | 6.3 | AWG 22 - 8 |

| Conductor cross section solid (min.-max.) | Conductor cross section stranded (min.-max.) | 2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.) | AWG Conductor | Insulation Stripping Length | Torque (min.-max.) | Screwdriver |
|---|--|---|---------------|-----------------------------|--------------------|-------------|
| 0.34 - 10 mm ² | 0.2 - 6 mm ² | 0.5 - 4 mm ² | AWG 22 - 8 | 9 - 10 mm | 0.5 - 0.8 Nm | 0.8 x 3.5 |

| Rated Impulse Voltage | Insulation material group / Gauge per code according to IEC 60947-1 | Protection class / Protection conductor type |
|-----------------------|---|--|
| 6/3 | 1/B5 | IP 20/ - |

| Diode Voltage | Diode Current | Diode |
|---------------|---------------|-------|
| | | |

| Terminal | Qty. | End Plate | Qty. |
|------------|------|-----------|------|
| ERTD6BEIGE | 20 | | |
| ERTD6GREY | 20 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| CCS4/2 | 25 | | |
| CCS4/3 | 20 | | |
| CCS4/4 | 15 | | |
| CCS4/10 | 5 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES7xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| | | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/10 | 200 | DG10/6 | 360 |

| Voltage, V ~ | Current, A | Cross Section |
|--------------|------------|-------------------|
| 500 | 16 | 4 mm ² |

| Conductor cross section solid (min.-max.) | Conductor cross section stranded (min.-max.) | 2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.) | AWG Conductor | Insulation Stripping Length | Torque (min.-max.) | Screwdriver |
|---|--|---|---------------|-----------------------------|--------------------|-------------|
| 0.2 - 6 mm ² | 0.2 - 4 mm ² | 0.5 - 2.5 mm ² | AWG 24 - 10 | 9 - 10 mm | 0.5 - 0.8 Nm | 0.8 x 3.5 |

| Rated Impulse Voltage | Insulation material group / Gauge per code according to IEC 60947-1 | Protection class / Protection conductor type |
|-----------------------|---|--|
| 6/3 | 1/A4 | IP 20/ - |

| Diode Voltage | Diode Current | Diode |
|---------------|---------------|-------|
| | | |

| Terminal | Qty. | End Plate | Qty. |
|------------|------|-----------|------|
| ERTD3BEIGE | 20 | EPF3BEIGE | 10 |
| ERTD3GREY | 20 | EPF3GREY | 10 |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| CCS4/2 | 25 | | |
| CCS4/3 | 20 | | |
| CCS4/4 | 15 | | |
| CCS4/10 | 5 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| ES7xx | 100 | | |
| ES4xx | 100 | | |
| ES7xx | 50 | | |

| With Symbol | Qty. | Without Symbol | Qty. |
|-------------|------|----------------|------|
| | | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| GM | 50 | GM3 | 50 |
| GM1-1 | 25 | | |
| GM2-1 | 25 | | |
| GM2-2 | 25 | | |

| Part Number | Qty. | Part Number | Qty. |
|-------------|------|-------------|------|
| DG10/6 | 360 | DG10/6 | 360 |



4 mm² Knife Disconnect Terminal Block with Socket, Lever and Busbar For 25 mm DIN Rail

4 mm² Disconnect Terminal Block with Busbar For 25 mm DIN Rail



| Electrical Ratings | Voltage, V ~ | | | Current, A | | | Cross Section | | |
|---|--------------|------|----------------|---------------|-------------|------|----------------|------|--|
| | 500 | | | 15 | | | 4 mm² | | |
| CE (EN 60947-7-1) | | | | | | | | | |
| UL/ULC (IEC 60947-7-1) | | | | | | | | | |
| VDE (IEC 60947-7-1) | | | | | | | | | |
| CSA | | | | | | | | | |
| ESCC | | | | | | | | | |
| Dimensional Data | | | | | | | | | |
| Conductor cross section solid (min.-max.) | | | | 0.2 - 6 mm² | | | 0.2 - 6 mm² | | |
| Conductor cross section stranded (min.-max.) | | | | 0.2 - 6 mm² | | | 0.2 - 6 mm² | | |
| 2 Conductors with same cross section, stranded. With terminals with plastic sleeve, (min.-max.) | | | | 0.5 - 2.5 mm² | | | 0.5 - 2.5 mm² | | |
| AWG Conductor | | | | AWG 24 - 10 | | | AWG 24 - 10 | | |
| Insulation Stripping Length | | | | 9 - 10 mm | | | 8 - 9 mm | | |
| Torque (min.-max.) | | | | 0.5 - 0.8 Nm | | | 0.5 - 0.8 Nm | | |
| Screwdriver | | | | 0.8 x 3.5 | | | 0.8 x 3.5 | | |
| Technical Data | | | | | | | | | |
| Rated Impulse Voltage | | | | 6/3 | | | 6/3 | | |
| Insulation material group / Gauge per code according to IEC 60947-1 | | | | 1/A4 | | | 1/A4 | | |
| Protection class / Protection conductor type | | | | IP 20 - | | | IP 20 - | | |
| Diode Technical Data | | | | | | | | | |
| Diode Voltage | | | | | | | | | |
| Diode Current | | | | | | | | | |
| Diode | | | | | | | | | |
| Ordering Data | | | | | | | | | |
| Range | | | | | | | | | |
| Grey | | | | | | | | | |
| Cross Connection - Comb Connection | | | | | | | | | |
| | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | |
| | CCS4/2 | 25 | | | CCS6/2 | 25 | | | |
| | CCS4/3 | 20 | | | CCS6/3 | 20 | | | |
| | CCS4/4 | 15 | | | CCS6/4 | 15 | | | |
| | | | | | CCS6/10 | 5 | | | |
| End Bracket | | | | | | | | | |
| xx Range or Grey | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | |
| | ES7xx | 100 | | | ES7xx | 100 | | | |
| | ES4xx | 100 | | | ES4xx | 100 | | | |
| | ES7xx | 50 | | | ES7xx | 50 | | | |
| Test Plug and Sockets | | | | | | | | | |
| | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | |
| Warning Label | | | | | | | | | |
| Available in White and Yellow | With Symbol | Qty. | Without Symbol | Qty. | With Symbol | Qty. | Without Symbol | Qty. | |
| Group Marking | | | | | | | | | |
| | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | |
| | GM | 50 | GMS | 50 | | | | | |
| | GM1-1 | 25 | | | | | | | |
| | GM1-2 | 25 | | | | | | | |
| | GM2-2 | 25 | | | | | | | |
| Unprinted Markers | | | | | | | | | |
| | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | Part Number | Qty. | |
| | DS10/5 | 360 | | | | | | | |

THE WORLD'S SMALLEST. THE WORLD'S BEST.

IMO offers a comprehensive range of high-quality Contactors, suited to a range of applications. Regular switching requirements are more than adequately handled by our proven "Standard" 3 or 4 pole devices, while dedicated designs are available for switching DC loads (PV applications, Capacitor / Battery banks) and low current loads (LED lighting, Vehicles etc.).

Our ground-breaking Mini and Micro Contactors offer the same feature-driven benefits as the Standard range, with a smaller footprint to facilitate miniaturisation.

Modular Contactors offer almost silent switching in a compact, distribution-board friendly package; useful in the home or office environment where noise and aesthetics are a concern.

All of our Contactors are partnered with a full range of accessories and options to add functionality and flexibility to your design. Isn't it time you made the Switch to IMO Contactors?

- Full range from Micro to Mega Contactors
- International Approvals (EN/IEC, UL, CSA, etc)
- Cutting-edge designs including miniaturised
- Full range of accessories and options including PCB mounting



Scan this QR code using your smartphone to view our Micro Contactors