

piGRIP® G.S70T60.F.S1.XXX.00



- ▶ Configurable suction cup with recyclable parts. The different hardness makes the suction cup stable and at the same time soft and flexible.
- ▶ Durable and long lasting material with higher lifting capacity compared to similar conventional cups.
- ▶ Mark free and oil resistant lip material, suitable for smooth surfaces such as glass and metal.
- ▶ Suitable for flat or slightly curved objects. Cleats prevent thin, sensitive objects from being deformed.

Lifting force

Description	Vertical		Parallel	
	40 -kPa	60 -kPa	40 -kPa	60 -kPa
Lifting forces	103.5 N	148.0 N	51.8 N	74.0 N

Technical data

Description	Unit	Value
Max. vertical movement	mm	5.1
Internal volume	cm ³	11.0
Weight	g	27.6
Min. Curve radius -60 kPa	mm	80

Material specification

Description	Material	Colour	Hardness °Shore A	Temperature range (°C)
Lip	TPE	Green	60	-20-60/100*
Support	TPE	Lime	87	-20-60/100*

*Max. Temperature short term contact, <10 seconds and 50% intermittence, ambient temperature 15-30°C, mechanical properties will start to degrade.

Material resistance

Description	FDA Approved	PWIS Free	Wear Resistance	Oil	Weather & Ozone
Lip	No	Yes	Excellent	Excellent	Excellent
Support	No	Yes	Excellent	Excellent	Excellent

Description	Hydrolysis	Petrol	Concentrated Acids	Alcohol	Oxidation
Lip	Fair	Poor	Poor	Good	Good
Support	Fair	Poor	Poor	Good	Good

Values specified in data sheet are tested at:

- Room temperature (20°C [68°F] ± 3°C [5.5°F]).
- Standard atmosphere (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]).

- Relative humidity 20-70%.
- Compressed air quality, DIN ISO 8573-1 class 4.

Dimensional drawing



Description	Unit	Value
Building height	mm	17.8
Diameter (lip)	mm	70

Ordering information

Description	Product code
piGRIP®, Ø 70 mm Standard lip, TPE 60° Shore A, Green, No bellows, Support S1, Without fitting, No Size, None, No Option, None	G.S70T60.F.S1.XXX.00

Ordering information, spare parts

Description	Art. No.
Ø 70 mm Standard lip, TPE 60° Shore A	0121996