



Button-Head Screws ISO 7380


- High-strength standard screws for the MB Building Kit System
- Specifically suitable for use in the profile groove

4

The following applies to all the products below:

St

Property class 10.9 (bright zinc-plated designs)



Button-Head Screw M4x8

a = 8 mm m = 1.1 g

bright zinc-plated, 1 pce.

8.0.001.98

Button-Head Screw M4x10

a = 10 mm m = 1.3 g

bright zinc-plated, 1 pce.

8.0.002.01

Button-Head Screw M4x12

a = 12 mm m = 1.5 g

bright zinc-plated, 1 pce.

8.0.002.04

Button-Head Screw M4x14

a = 14 mm m = 1.6 g

bright zinc-plated, 1 pce.

8.0.002.07

Button-Head Screw M4x16

a = 16 mm m = 1.8 g

bright zinc-plated, 1 pce.

8.0.000.05

Button-Head Screw M4x18

a = 18 mm m = 2.0 g

bright zinc-plated, 1 pce.

8.0.002.10

Button-Head Screw M4x20

a = 20 mm m = 2.2 g

bright zinc-plated, 1 pce.

8.0.002.13

Button-Head Screw M4x22

a = 22 mm m = 2.4 g

bright zinc-plated, 1 pce.

8.0.002.16

Button-Head Screw M4x25

a = 25 mm m = 2.7 g

bright zinc-plated, 1 pce.


8.0.002.19

Button-Head Screw M4x30

a = 30 mm m = 3.1 g

bright zinc-plated, 1 pce.

8.0.002.22



Button-Head Screw M5x8

a = 8 mm m = 1.8 g

bright zinc-plated, 1 pce.

8.0.000.24

Button-Head Screw M5x10

a = 10 mm m = 2.0 g

bright zinc-plated, 1 pce.

8.0.000.06

Button-Head Screw M5x12

a = 12 mm m = 2.3 g

bright zinc-plated, 1 pce.

8.0.005.45

Button-Head Screw M5x14

a = 14 mm m = 2.6 g

bright zinc-plated, 1 pce.

0.0.417.30

Button-Head Screw M5x16

a = 16 mm m = 2.8 g

bright zinc-plated, 1 pce.

8.0.000.07

Button-Head Screw M5x18

a = 18 mm m = 3.0 g

bright zinc-plated, 1 pce.

8.0.002.25

Button-Head Screw M5x20

a = 20 mm m = 3.2 g

bright zinc-plated, 1 pce.

0.0.404.11

Button-Head Screw M5x25

a = 25 mm m = 3.8 g

bright zinc-plated, 1 pce.

8.0.000.25

Button-Head Screw M5x30

a = 30 mm m = 4.4 g

bright zinc-plated, 1 pce.

8.0.002.31

Button-Head Screw M5x35

a = 35 mm m = 5.0 g

bright zinc-plated, 1 pce.

8.0.002.34

Button-Head Screw M5x40

a = 40 mm m = 5.6 g

bright zinc-plated, 1 pce.


0.0.391.26

Button-Head Screw M5x45

a = 45 mm m = 6.2 g

bright zinc-plated, 1 pce.

8.0.005.24



Button-Head Screw M6x10

a = 10 mm m = 2.8 g

bright zinc-plated, 1 pce.

8.0.002.37

Button-Head Screw M6x12

a = 12 mm m = 3.2 g

bright zinc-plated, 1 pce.

8.0.002.40

Button-Head Screw M6x14

a = 14 mm m = 3.6 g

bright zinc-plated, 1 pce.

0.0.417.26

Button-Head Screw M6x16

a = 16 mm m = 3.8 g

bright zinc-plated, 1 pce.

8.0.000.63

Button-Head Screw M6x18

a = 18 mm m = 4.2 g

bright zinc-plated, 1 pce.

8.0.002.45

Button-Head Screw M6x20

a = 20 mm m = 4.5 g

bright zinc-plated, 1 pce.

8.0.000.08

Button-Head Screw M6x22

a = 22 mm m = 4.9 g

bright zinc-plated, 1 pce.

8.0.002.48

stainless, 1 pce.

8.0.005.56

Button-Head Screw M6x25

a = 25 mm m = 5.4 g

bright zinc-plated, 1 pce.

8.0.000.01

Button-Head Screw M6x30

a = 30 mm m = 6.2 g

bright zinc-plated, 1 pce.

8.0.000.15

Button-Head Screw M6x35

a = 35 mm m = 7.1 g

bright zinc-plated, 1 pce.

8.0.000.16

Button-Head Screw M6x40

a = 40 mm m = 7.9 g

bright zinc-plated, 1 pce.

8.0.001.15

Button-Head Screw M6x45

a = 45 mm m = 8.8 g

bright zinc-plated, 1 pce.


8.0.002.53

Button-Head Screw M6x50

a = 50 mm m = 9.6 g

bright zinc-plated, 1 pce.

8.0.002.56

**Button-Head Screw M8x10**

a = 10 mm m = 4.4 g

bright zinc-plated, 1 pce.

8.0.000.17

Button-Head Screw M8x12

a = 12 mm m = 5.1 g

bright zinc-plated, 1 pce.

8.0.002.59

Button-Head Screw M8x14

a = 14 mm m = 6.1 g

bright zinc-plated, 1 pce.

8.0.000.18

Button-Head Screw M8x16		
a = 16 mm	m = 7.2 g	
bright zinc-plated, 1 pce.		8.0.000.19
Button-Head Screw M8x18		
a = 18 mm	m = 7.4 g	
bright zinc-plated, 1 pce.		8.0.000.02
Button-Head Screw M8x20		
a = 20 mm	m = 8.6 g	
bright zinc-plated, 1 pce.		8.0.009.11
Button-Head Screw M8x25		
a = 25 mm	m = 10.1 g	
bright zinc-plated, 1 pce.		8.0.000.04
Button-Head Screw M8x30		
a = 30 mm	m = 12.0 g	
bright zinc-plated, 1 pce.		8.0.000.09
Button-Head Screw M8x35		
a = 35 mm	m = 13.9 g	
bright zinc-plated, 1 pce.		8.0.002.65
Button-Head Screw M8x40		
a = 40 mm	m = 15.8 g	
bright zinc-plated, 1 pce.		8.0.000.10
Button-Head Screw M8x45		
a = 45 mm	m = 17.9 g	
bright zinc-plated, 1 pce.		8.0.000.20
Button-Head Screw M8x50		
a = 50 mm	m = 19.6 g	
bright zinc-plated, 1 pce.		8.0.002.68
Button-Head Screw M8x55		
a = 55 mm	m = 21.5 g	
bright zinc-plated, 1 pce.		8.0.002.71
Button-Head Screw M8x60		
a = 60 mm	m = 23.5 g	
bright zinc-plated, 1 pce.		8.0.000.11
Button-Head Screw M8x80		
a = 80 mm	m = 27.7 g	
bright zinc-plated, 1 pce.		8.0.000.12




Cap, Button-Head Screw

- Protect screws and screw heads from dirt and corrosion
- For use with item Button-Head Screws M6 and M8




4

The Caps cover the hexagon socket of the screw head and the gap around the screw connection. They are suitable for Button-Head Screws and button-head flange screws.



Application of the Cap, Button-Head Screw M6 on Button-Head Screws used to fasten panel elements to Multiblocks.




Cap, Button-Head Screw M6



PA-GF
m = 0.4 g

grey similar to RAL 7042, 1 pce.

0.0.606.61



Cap, Button-Head Screw M8



PA-GF
m = 0.9 g

grey similar to RAL 7042, 1 pce.

0.0.606.67




Hexagon Socket Head Cap Screws


- Screws for universal use
- Various diameters and lengths
- High property class of 10.9

The following applies to all the products below:

St
property class 10.9



Hexagon Socket Head Cap Screw DIN 912 M3x50		
a = 50 mm	b = 18 mm	m = 2.9 g
black, 1 pce.		
8.0.004.61		




Hexagon Socket Head Cap Screw DIN 912 M3x60		
a = 60 mm	b = 18 mm	m = 3.3 g
black, 1 pce.		
8.0.004.83		

Hexagon Socket Head Cap Screw DIN 912 M4x14		
a = 14 mm	b = 14 mm	m = 2.0 g
bright zinc-plated, 1 pce.		
8.0.000.21		

Hexagon Socket Head Cap Screw DIN 912 M4x16		
a = 16 mm	b = 16 mm	m = 2.1 g
bright zinc-plated, 1 pce.		
8.0.000.28		

Hexagon Socket Head Cap Screw DIN 912 M4x18		
a = 18 mm	b = 18 mm	m = 2.2 g
bright zinc-plated, 1 pce.		
8.0.000.22		

Hexagon Socket Head Cap Screw DIN 912 M4x20		
a = 20 mm	b = 20 mm	m = 2.4 g
bright zinc-plated, 1 pce.		
8.0.000.23		



Hexagon Socket Head Cap Screw DIN 912 M6x12		
a = 12 mm	b = 12 mm	m = 5.0 g
bright zinc-plated, 1 pce.		
8.0.007.16		

Hexagon Socket Head Cap Screw DIN 912 M6x14		
a = 14 mm	b = 14 mm	m = 5.4 g
bright zinc-plated, 1 pce.		
8.0.007.99		

Hexagon Socket Head Cap Screw DIN 912 M6x20		
a = 20 mm	b = 20 mm	m = 6.0 g
bright zinc-plated, 1 pce.		
8.0.000.92		

Hexagon Socket Head Cap Screw DIN 912 M6x28		
a = 28 mm	b = 24 mm	m = 7.5 g
bright zinc-plated, 1 pce.		
0.0.411.59		

Hexagon Socket Head Cap Screw DIN 912 M6x100

a = 100 mm b = 24 mm m = 23.0 g

bright zinc-plated, 1 pce.


8.0.004.70

Hexagon Socket Head Cap Screw DIN 912 M6x140

a = 140 mm b = 24 mm m = 31.5 g

bright zinc-plated, 1 pce.

8.0.004.74

**Hexagon Socket Head Cap Screw DIN 912 M8x60**

a = 60 mm b = 28 mm m = 29.0 g

bright zinc-plated, 1 pce.


8.0.006.36

Hexagon Socket Head Cap Screw DIN 912 M8x180

a = 180 mm b = 28 mm m = 66.5 g

bright zinc-plated, 1 pce.

8.0.008.88

**Hexagon Socket Head Cap Screw DIN 912 M10x60**

a = 60 mm b = 32 mm m = 44.0 g

bright zinc-plated, 1 pce.

8.0.003.98

Hexagon Socket Head Cap Screw DIN 912 M10x100

a = 100 mm b = 32 mm m = 68.5 g

bright zinc-plated, 1 pce.


8.0.004.47

Hexagon Socket Head Cap Screw DIN 912 M10x140

a = 140 mm b = 32 mm m = 92.5 g

bright zinc-plated, 1 pce.


8.0.004.50

**Hexagon Socket Head Cap Screw DIN 6912 M5x8**

a = 8 mm b = 8 mm m = 2.6 g

bright zinc-plated, 1 pce.

8.0.004.34

**Hexagon Socket Head Cap Screw DIN 6912 M6x40**

a = 40 mm b = 24 mm m = 9.5 g

bright zinc-plated, 1 pce.

8.0.007.43




Countersunk Screws DIN 7991

- For screw connections that are flush with the surface of components and panel elements

The following applies to all the products below:

St
property class 10.9




Countersunk Screw DIN 7991 M5x10

a = 10 mm m = 1.8 g

black, 1 pce.

8.0.001.84




Countersunk Screw DIN 7991 M6x10

a = 10 mm m = 2.7 g

black, 1 pce.

8.0.007.48



Countersunk Screw DIN 7991 M8x14

a = 14 mm m = 7.1 g

black, 1 pce.

8.0.007.07

Countersunk Screw DIN 7991 M8x16

a = 16 mm m = 7.4 g

bright zinc-plated, 1 pce.

8.0.001.09

Countersunk Screw DIN 7991 M8x18

a = 18 mm m = 7.7 g

black, 1 pce.

8.0.001.85